



SERIE Maxi	TECHNICAL FEATURES	
	SERIE 9 MAXI	SERIE 10 MAXI
<b>DIESEL ENGINE</b>	John Deere 6800 cc, 138 kw (185 hp), Turbo intercooler, Common Rail, 6-cylinder TIER 3A (for non-EU Countries) FPT NEF 6700 cc, 151 kw (205 hp), 6-cylinder, Turbo intercooler, STAGE V, AdBlue (for EU Countries)	
<b>DRIVE SYSTEM</b>	Hydrostatic pump, 4-wheel drive, with Poclain hydraulic motors on the wheels	
<b>SPRAY TANK CAPACITY</b>	3500 L or 4000 L	4000 L oppure 4500 L
<b>SUSPENSIONS</b>	Active pneumatic system + hydraulic front and rear, pneumatic on boom parallelogram	
<b>BRAKES</b>	PARKING BRAKE: Passive electric brake at the rear wheels SERVICE BRAKE: hydraulic brakes at the rear wheels	
<b>GEAR BOX</b>	Electro-hydraulic, 2 speed (0-20 km/h, 0-40 km/h)	
<b>STEERING SYSTEM</b>	4 steering wheels with 4 steering modes	
<b>CAB</b>	Class IV, pressurized, air conditioned, heated, n°2 activated carbon filters and pneumatic driver's sea	
<b>COMPUTER</b>	ARAG or TRIMBLE with or without GPS	
<b>CLEARANCE</b>	1550 mm or 1700 or 1800 mm	
<b>BOOM</b>	Steel 24 - 27 - 28 – 30 m (optional air assisted 24 - 27 – 28 m) Aluminium 24 - 28 - 30 - 32 - 36 m (optional air assisted 24 - 28 – 30 m)	Steel 24 - 27 - 28 – 30 m (optional air assisted 24 - 27 – 28 m) Aluminium 24 - 28 - 30 - 32 - 36 m (optional air assisted 24 - 28 – 30 m)
<b>DIMENSIONS</b>	Lenght: 8200 mm Width: 2550 mm (2700 mm aluminium) Height: 4200 mm Wheelbase: 3200 mm	Lenght: 8800 mm Width: 2550 mm (2700 mm aluminium) Height: 4450 mm Wheelbase: 3650 mm
<b>TARE</b>	8400 – 8700 kg	8700 – 8900 kg
<b>TYRES</b>	270, 300, 310, 320, 340, 380, 420, 480	